

# PM5

## FULL SCANNING CAPABILITY RIGHT ON YOUR FINGER

### Our newest wearable scanner making heavy-duty light

Point Mobile’s mobile computers are powerful, and capable of processing and transferring data fast. But sometimes your workforces need to be deployed in scanning-only tasks for hours, in which case using a heavy device can be exhausting. With the incredibly light and ambidextrous form factor that fits perfectly on your finger, the PM5 was built for heavy and long scanning tasks.

### Easy pair to use the full power of mobile computers

Equipped with power-efficient Bluetooth v4.2 supporting BLE, the PM5 can operate up to 8h with standard 510mAh battery. Optional extended battery with 700mAh pushes the uptime further to 11h. This also allows fast and no-delay data transfer to Point Mobile’s rugged computing devices. All you have to do for pairing is just one tap – and enjoy the lightweight and convenience of a ring scanner while using all the computing power and the enterprise mobility solutions that Point Mobile offers.

### Don't stop moving just to scan a barcode

Inside of PM5 lies an ultra-slim 2D imager which can tolerate motion speed of up to 6.0 m/s, easily capturing fast-moving objects with accuracy. You can also scan while moving your hands, making no interruption on your workflow. The scan engine has one of the lowest power demands in its class, increasing the battery life of the PM5 even further.

### Rugged for any industrial applications

The PM5 is a rugged scanner designed to withstand harsh working environments. It can survive multiple drops to concrete from 1.8m/6 ft. over the operating temperature range and is equipped with IP65 grade water/dust resistance. You can operate the device in temperatures from 0°C to 50°C. And the loud 85 dBA buzzer will make sure you'll notice when you've successfully scanned - even in noisy work environments. PM5 comes with programmable LEDs for perfect integration and customization.



### Industries

- Retail
- Warehouse Management
- Field Services
- Transport & Logistics

### Accessories

- |                            |                           |
|----------------------------|---------------------------|
| <b>Standard</b>            | <b>Optional</b>           |
| Battery STD 510 mAh        | Extended Battery (700mAh) |
| Ring Trigger or USB-C Sled | 4 Slot Ring Charger       |
|                            | 8 Slot Battery Charger    |
|                            | 20 Slot Ring Charger      |
|                            | 40 Slot Battery Charger   |



Tap to pair



Imager



Light Weight



Bluetooth 4.2



IP65



Ambidextrous ring trigger



STD 510 mAh  
EXT 700 mAh



Buzzer to 85 dBA



From 1,8 m  
6 ft

# PM5

## PERFORMANCE CHARACTERISTICS

### Main processor

32-bit ARM® Cortex® processor, up to 120MHz

### Firmware

RTOS Upgradable via USB or Bluetooth

### Supported Host OS

Android, Windows

### Memory and Storage

RAM 128 KB  
ROM 1 MB (PGM), 16 MB storage

## PHYSICAL CHARACTERISTICS

### Dimensions

With STD battery 61 mm L x 28 mm W x 21 mm D  
2.4 in L x 1.1 in W x 0.8 in D

### Weight

With ring trigger Battery STD 49 g  
Battery EXT 52 g

### Without ring trigger

Battery STD 35 g  
Battery EXT 38 g

### Power

Battery STD 4,35 V, 510 mAh (removable)  
Battery EXT 4.35V, 700 mAh Li-ion (removable)

### Keys

Reset Key Device reboot or factory reset

### Standard Communications

USB Type-C (ring trigger)

### Notification

LED 2 programmable LEDs (back side)  
Buzzer Up to 85dBA (back side)

## WIRELESS

### Wireless PAN

Bluetooth Integrated Bluetooth Class I-II, Ver. 4.2  
BLE support  
Tap to Pair  
Supported Profiles: Serial Port Profile (SPP),  
Human Interface Profile (HID), Service  
Discovery Application Profile (SDAP)

## DATA CAPTURE

### Integrated Barcode Reader

Honeywell N6703 Ultra slim 1D/2D barcode scan engine

## USER ENVIRONMENT

**Operating Temperature** 0°C to 50°C / 32 °F to 122°F

**Storage Temperature** -40°C to 70°C / -40°F to 158°F

**Humidity** 95% Non-condensing

**Drop** Multiple 1.8m/6ft. drops to concrete over operating temperature range

**Rain /Dust Proof (Sealing)** IP65

**Tumble** 1,000 cycles at 0.5m / 1.64ft

**Electrostatic Discharge** ±15 kV air discharge  
±8 kV direct discharge

## REGULATORY APPROVALS AND COMPLIANCE

Certified CE, FCC, IC, NOM, IFETEL, WPC, BIS, KC  
Environmental: RoHS III & WEEE compliant

## WARRANTY

Subject to the Terms and Conditions, PM5 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects. Point Special and Premium Care service is recommended.

For the further inquiry, please contact:  
serwis@epicmobile.pl



**AMBIDEXTROUS RING TRIGGER**



**IP65 WATER/DUST RESISTANCE**



**USB-C SLED (WITH LANYARD)**



**TAP-TO-PAIR**

For more information, visit [pm.epicmobile.eu](http://pm.epicmobile.eu) or [www.pointmobile.com](http://www.pointmobile.com)