

# **RF900**

## **ARM YOUR PM90 WITH** THE MOST PRODUCTIVE **UHF RFID READER**





**ACCESSORIES** 



Retail



**Industrial Production Process Control** 



Logistics / Warehouse Management



Medical / Pharmacy

### **Specifications**

# PHYSICAL CHARACTERISTICS

Standard 84.3 mm W x 166.3 L x 140.6 mm H Weight 463.5g with standard battery (only RF900) Power Battery 3,250 mAh 3.6V Li-ion, removable **Buttons** Trigger, Power, Trigger Mode, Connection Mode USB interface Standard Communications Power Supply 5V/2A adaptor Notification Charging LED, Status LED, Connect-Mode, Trigger-Mode LED, Vibration

### PERFORMANCE CHARACTERISTICS

Supported Protocol Standards

EPC Global UHF Class 1 Gen 2 V2 / ISO 18000-6C

**RFID Engine** Impinj® Indy® R2000 Nominal Read Range 6m+ (19.69ft+)

up to 900 tags per second **Fastest Read Rate** EU: 865MHz ~ 868MHz Frequency / RF Output = <30dBm (± 0.3dBm) US: 902MHz ~ 928MHz = <30dBm (± 0.3dBm)

Memory

160KB ROM 1MB

### **USER ENVIRONMENT**

Operating -10°C to 50°C Temperature Storage -40°C to 70°C Temperature Drop 1.5m to concrete Rain / Dust Proof

**WIRELESS** 

Bluetooth Bluetooth Ver. 4.2 BR/EDR/BLE NFC

# **Standard Accessories** AC/DC Power Adapter Country Plug USB Type-C Cable Hand-Strap Battery **Optional Accessories** Single Slot Cradle (charging only) 4 Slot Battery Charger

### **Corporate Headquarters**

Point Mobile Co., Ltd. pm\_sales1@pointmobile.com +82 2 3397 7870

### **NA Headquarters**

Point Mobile Americas LLC info@pointmobileamericas.com +1 425 780 4452

### **Europe Headquarters**

Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 6196 777 3666

### **China Headquarters**

Point Mobile China info@pointmobile.com.cn +86 755 8869 1169

### For more information, visit www.pointmobile.com